

DIMENSIONS

FRR / FVR

Delivering profit to you



MAIN SPECIFICATIONS

Class	FRR34L	FVR34P	FVR34Q
Model	FRR34L-02	FVR34P-02	FVR34Q-02
Suffix Code	FRR34SL-LCN	FVR34SL-PDN	FVR34SL-QDN
Rear Tire	Dual	Dual	Dual
G.V.W. [Kg]	10,400	15,100	15,100
Type	Cab chassis	Cab chassis	Cab chassis
Seating Capacity	3	3	3

ENGINE

Model	6HK1-TCN	6HK1-TCN	6HK1-TCN
Type	Direct Injection, OHC, Diesel		
Emission Level	Euro II	Euro II	Euro II
No. of cylinders	6	6	6
Displacement [cc]	7,790	7,790	7,790
Max. Output [PS/rpm]	240 / 2,400	240 / 2,400	240 / 2,400
Max. Torque [Kgf·m/rpm]	72.0 / 1,450	72.0 / 1,450	72.0 / 1,450
Starter	24V - 5.0KW	24V - 5.0KW	24V - 5.0KW

MASS (kg)

Cab Chassis / Vehicle Mass	3,495	4,790	4,865

CHASSIS

Clutch	Type	Dry Single Plate		
	Size [mm]	380	380	380
Transmission	Type	MZW6P		
	Diameter [inch]	14.5"	16.5"	16.5"
Final Gear	Gear Ratio	4.333	5.571	5.571
	Type	AOH		
Brake	Parking	Center Brake		
	Type	Power Assist		
Axle	Front	F036	F063	F063
	Rear	R077	R105	R105
Suspension		FR Multi Leaf Suspension & RR Multi Leaf Suspension		
Frame		840mm Straight	850mm Straight	850mm Straight
Tire	Front & Rear	8.25R16-14PR	10.00R20-14PR	10.00R20-14PR
Disc Wheel	Front & Rear	6STD 16X6.00GS	8STD 20X7.00T	8STD 20X7.00T
Fuel Tank Capacity [Liter]		200L	200L	200L

Unit:mm

MODEL	FRR34L-02	FVR34P-02	FVR34Q-02
REAR TIRE	Dual	Dual	Dual
TYPE	Cab chassis	Cab chassis	Cab chassis
OAL	7,255	8,505	9,255
OW	2,200	2,400	2,400
AW	1,790	2,445	2,445
CW	1,660	1,845	1,845
BW	2,165	2,445	2,445
FOH	1,170	1,440	1,440
WB	4,360	5,050	5,550
ROH (Frame end)	1,725	2,015	2,265
CA	3,464	4,424	4,924
CE	5,185	6,439	7,189
OH	2,600	2,880	2,880
FR Axle to cab end	896	626	626

